

## Oil-less, Portable Air Compressors

Westward® oil-less air compressors deliver convenience and solid performance for light-duty applications. The direct drive, oil-less pump design is virtually maintenance-free—no oil changes or drive belt replacements. They are ideal for small job uses such as nailers and staplers and for general maintenance work.



### Cordless Inflator

Portable air power

- Battery powered
- Operates from 12V vehicle outlet or 120V outlet
- Inflates to 250 psi max.
- Includes flashing hazard light and work light

Item No.	Description
4ME94	Cordless Inflator



### Tankless Air Compressor

Air power wherever you need it

Maintenance-free performer for light-duty applications. 115V, 60 Hz., 11 amp.

- Includes built-in regulator, 15 ft. air hose and tire chuck
- Delivers 2.6 CFM at 90 psi; 1.8 CFM (125 psi max.)

Item No.	Description
3JR69	.75 Running HP Tankless Air Compressor



### Oil-less Contractor Air Compressor

For air tools and general maintenance

Convenient, lightweight, and maintenance-free compressor is ideal for small home shop or contractor applications. 115 volt, 60 Hz. universal motor for improved start under low voltage conditions. Moving parts are concealed by durable plastic shroud. 11 amp. 135 max. psi.

- 3 gallon tank
- 1/4" (F)NPT outlet
- Air delivery—2.6 CFM @ 90 psi

Item No.	Description
3JR70	.75 Running HP Hotdog Compressor

## Portable and Contractor Air Compressors

Convenience and portability makes these Westward® contractor air compressors ideal for jobsite and general purpose applications. The oil-less pump is virtually maintenance-free with no oil to change or belts to replace.

### 20 Gallon Oil-less Portable Air Compressor

- 20 gallon ASME tank
- 1/4" (F)NPT outlet
- Air delivery—5.8 CFM @ 90 psi

Item No.	Description
3JR71	2 Running HP Portable Direct Drive Air Compressor



### Contractor Air Compressor

Operation at any angle

Lightweight pancake design makes carrying easy. Moving parts are concealed by durable plastic shroud.

- 4 gallon tank
- 1/4" (F)NPT outlet
- Air delivery—2.6 CFM @ 90 psi

Item No.	Description
4YD76	.75 Running HP Pancake Air Compressor

## Cast-Iron, Portable Air Compressors

Belt-driven, oil lubricated pump design makes these **Westward®** compressors an outstanding value. Designed for heavier duty applications, the cast-iron pump delivers solid performance and reliability. Ideal for a wide variety of applications including maintenance shops, construction jobsites, and spray painting.

### Portable Cast-Iron Air Compressor

Solid performance and reliability

Designed for heavier duty applications, the cast-iron construction features belt driven oil-lubricated pump, pressure regulator and two pressure gauges. Ideal for a wide variety of applications including maintenance shops, construction sites, and spray painting. 115/230V, 60 Hz., 15.7/7.5 amp., 125 max. psi.

- 13 gallon ASME tank
- 1/4" (F)NPT outlet
- Air delivery—5.5 CFM @ 90 psi

Item No.	Description
<b>3JR85</b>	2 Running HP Portable Electric Barrel Compressor



### Gas-Powered Cast-Iron Portable Air Compressor

When electric power is unavailable

Essential for areas such as jobsites, farms, and rural environments. Designed with rugged, cast-iron, two-cylinder pump and Briggs and Stratton Intek engine with overhead valves and recoil start. Automatic throttle control idles the engine while the pump is unloading.

- 3-quart gas tank
- 20 gallon ASME code tank
- 1/4" (F)NPT outlet
- Air delivery—9 CFM @ 90 psi

Item No.	Description
<b>4B220</b>	5.5 HP Gas-Powered Cast-iron Portable Air Compressor



### Portable Cast-Iron Air Compressor

Step up to cast-iron

Convenient vertical tank model saves space and features a cast-iron, oil-lubricated pump for heavier duty applications. Includes pressure regulator and 2 pressure gauges. 115/230V, 60 Hz., 15.7/7.5 amp. 125 max. psi.

- 20 gallon ASME tank
- 1/4" (F)NPT outlet
- Air delivery—5.5 CFM @ 90 psi

Item No.	Description
<b>4TW29</b>	Running HP Portable Air Compressor

## Westward® Portable Air Compressor Specifications

Model	Running HP	Free Air CFM @ 90 psi	Max. psi	Volts, Ph. 60 Hz	Amp Draw	Pump Type	Tank Gallons
<b>4ME94</b>	—	—	250	120 VAC/12 VDC	—	Oil-less	—
<b>3JR69</b>	.75	2.6	125	115	11	Oil-less	—
<b>3JR70</b>	.75	2.6	135	115	11	Oil-less	3
<b>4YD76</b>	.75	2.6	135	115	11	Oil-less	4
<b>3JR71</b>	2	5.8	135	115	15	Oil-less	20
<b>3JR85</b>	2	5.5	125	115/230	15.7/7.5	Oil-lube	13
<b>4TW29</b>	2	5.5	125	115/230	15.7/7.5	Oil-lube	20
<b>4B220</b>	5.5	9.0	110	Gas Engine	—	Oil-lube	20



Exclusively from Grainger.

## 1/2" Air Impact Wrenches

Built-in power regulator for convenient output adjustment

Features steel impact housing, ring type socket retainer and 1/4" NPT inlet size. Rubber grip for improved operator comfort.

### 5ZL12 1/2" Impact Wrench

- 7,000 RPM free speed
- 250 ft. lbs. torque
- Rubber housing band and nose piece
- 3/8" min. hose size
- Overall length 7"

### 5ZL17 1/2" Impact Wrench

- 7,500 RPM free speed
- 380 ft. lbs. torque
- 3/8" min. hose size
- Overall length 7-1/2"

Item No.	Description	Average CFM
5ZL12	1/2" Air Impact Wrench	6
5ZL17	1/2" Air Impact Wrench	7



5ZL12



5ZL17



## 3/8" Butterfly Impact Wrench

Compact size for use in tight areas

Features a swivel inlet with a built-in power regulator for convenient power output adjustment, butterfly throttle, ring type retainer, and 1/4" NPT inlet size.

- 10,000 RPM free speed
- 75 ft. lbs. max. torque
- 3/8" min. hose size
- Overall length 5-7/8"

Item No.	Description	Average CFM
5ZL18	3/8" Air Impact Wrench with Butterfly Throttle	4



## 1/2" Heavy-Duty Air Ratchet Wrench

When you require a heavy-duty fastening tool

Steel ratchet housing with front exhaust directs air away from operator. Head width 2", and 1/4" NPT inlet size.

- 150 RPM free speed
- 90 ft. lbs. max. torque
- 3/8" min. hose size
- Overall length 14"

Item No.	Description	Average CFM
5ZL21	1/2" Heavy Duty Air Ratchet	8



## 3/8" Air Ratchet Wrench

Features hardened steel mechanism for long life

1-5/8" wide ratchet head width and ball type socket retainer. 1/4" NPT inlet size. Rubber grip for improved operator comfort.

- 150 RPM free speed
- 50 ft. lbs. max. torque
- 3/8" min. hose size
- Overall length 10-1/2"

Item No.	Description	Average CFM
5ZL11	3/8" Air Ratchet Wrench	4.8



## 1/4" Air Ratchet Wrench

Features triple idler gear design for smooth operation

1-1/8" wide ratchet head width and ball type socket retainer. 1/4" NPT inlet size.

- 150 RPM free speed
- 18 ft. lbs. max. torque
- 3/8" min. hose size
- Overall length 6-1/2"

Item No.	Description	Average CFM
5ZL16	1/4" Air Ratchet Wrench	3.1

## 1/2" Air Impact Wrench Kit

Delivers 60–200 ft/lbs. of working torque

Steel anvil housing and ring type retainer for fast socket changes.

- Oil bath clutch lubrication
- 7,000 RPM free speed
- 1,300 impacts per minute

**Kit Includes:**

5ZL12 Impact Wrench, 10" Impact Sockets in the following sizes: 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16 and 1". Also includes 2 oz. In Line Oiler and Plastic Carrying Case.

Item No.	Description	Average CFM
5ZR88	1/2" Air Impact Wrench Kit	6



5ZL30

## Air-Powered Cut-Off Tool and Tool Kit

Light-duty reliable tool for home workshop or general maintenance

Powerful 1/2 HP motor provides 22,000 RPM at 90 PSI. Cuts through clamps, bolts and 3/4" steel rod. Steel guard and safety lock-off lever on throttle prevents accidental starts.

- 3/8-24" spindle and 1/4" NPT inlet
- 3/8" min. hose size

**5ZL30 Kit Includes:**

Cut-Off Tool (5ZL29), 8 Cut-Off Wheels and Durable Plastic Case.

Item No.	Description	Average CFM
5ZL29	Air-Powered Cut-Off Tool	6
5ZL30	Air-Powered Cut-Off Tool Kit	6

## 3/8" Air Ratchet Wrench Kit

Convenient and portable

Tight areas are easy to access. Run fasteners in fenders or under dashboard in and out quickly.

- Steel ratchet housing for long life
- Triple idler gear design for smooth operation

**Kit Includes:**

5ZL11 Ratchet Wrench, 3" Extension Bar, 13/16" Spark Plug with 6 Point SAE and Metric Sockets in 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4", 9, 10, 11, 12, 13, 14, 16, 17 and 19 mm, and Plastic Carrying Case.

Item No.	Description	Average CFM
5ZR89	3/8" Air Ratchet Wrench Kit	4.8



## 5" High Speed Air Sander

Sand large amounts of materials quickly

Light grinding of metals for preparation of body fillers and rust removal. Variable speed throttle with muffled exhaust has 7/16-20" spindle, and 1/4" NPT inlet size.

- 2 HP industrial designed motor with low friction coefficient and high resistance to wear
- 18,000 RPM free speed
- Includes 3", 4-1/2" and 5" diameter backing discs
- 3/8" min. hose size
- Overall length 5-3/4"

Item No.	Description	Average CFM
5ZL19	5" High Speed Air Sander	5.7



## Air Screwdriver

Versatile tool for various uses

Ideal for wood screws, wall boards, assembly linework and setting aluminum windows and doors. 1/4" hex chuck. Reversible variable speed throttle. Adjustable cushion clutch.

- 1,800 RPM free speed
- 20–40 in. lbs. max. torque
- 1/4" NPT inlet size
- 3/8" min. hose size
- Overall length 9-1/4"

Item No.	Description	Average CFM
3BE27	Air Screwdriver	3





6PA55

### Air Tool Combination Kits

14-Piece — Impact Wrench and Air Hammer Kit

**6PA55 Kit Includes:**

- (2) Flip Sockets (3/4 and 3/16"), (1) 3" Extension Bar (1/2" Dr.), (3) 1/4" Plugs, (1) OSHA Blow Gun, with safety nozzle, (1) Tool Oil, (4) Chisels, (1) Spring Retainer, Blow-Molded Case.

18-Piece — Impact Wrench and Air Ratchet Kit

**6PA57 Kit Includes:**

- (10) Sockets, (1) Industrial Plug, (1) 3" Extension (1/2" Dr.), (1) 3/8" to 1/2" Adapter, (2) Flip Sockets (3/4 and 3/16"), (1) Air Tool Oil, High-Impact Molded Case.



6PA59

38-Piece — Straight Die Grinder, Air Hammer, Cut-off Tool Kits

**6PA59 Kit Includes:**

- (4) Air Hammer Chisels, (5) Grinding Wheels, (4) Wrenches, (7) Cut-off Discs, (2) Chisel Springs, (1) Tire Chuck, (5) 1/4" Male Plugs, (1) 1/4" Female Coupler, (1) Blow Gun w/ (5) Accessories, (1) Teflon Tape, High Impact Case.

Item No.	Description
6PA55	14-Piece Air Tool Kit
6PA57	18-Piece Air Tool Kit
6PA59	38-Piece Air Tool Kit



### Air Hammer Kit

For general maintenance and workshop use

This tool features a quick change retainer which allows for easy replacement of chisels. 5,000 blows per minute, 1-5/8" stroke length.

- Heat-treated steel piston and barrel for long life
- Uses standard .401" taper shank chisels
- 1/4" NPT inlet size
- 3/8" min. hose size

**Kit Includes:**

Air Hammer **5ZL24** with 4 Chisels, Tapered Punch Panel Cutter, Flat Chisel, Spot Weld Splitter, and Case.

Item No.	Description	Average CFM
5ZL25	Air Hammer Kit	5.5



5ZL27

### Reversible Air-Powered Drills

Economical alternative for home shop or light maintenance applications

Geared for high torque. 1/4" NPT inlet size.

- Features a Jacobs chuck and key with thumb operated forward/reverse switch. Rubber grip for improved operator comfort.

**5ZL27:**

- 1/2 HP motor
- 3/8" chuck
- Triple planetary gears for smooth operation
- Through handle exhaust reduces noise and chip flyback
- 2,200 RPM free speed
- 3/8" min. hose size
- Overall length 6-1/2"



5ZL26

**5ZL26:**

- 1/2" chuck
- Powerful 1/2 HP motor prevents stall under load
- Dead handle for increased operation control
- 500 RPM free speed
- 3/8" min. hose size
- Overall length 8-1/4"

Item No.	Description	Average CFM
5ZL27	3/8" Air-Powered Reversible Drill	6.6
5ZL26	1/2" Air-Powered Reversible Drill	6



### Right Angle Air-Powered Die Grinder

Designed for grinding and deburring operations in confined areas

1/4 HP motor features a built-in regulator for speed control. Lock-off lever throttle prevents accidental starts and rear exhaust directs air away from work surface. Rubber grip for improved operator comfort.

- 1/4" collet size
- 18,000 RPM free speed
- 1/4" NPT air inlet
- 3/8" min. hose size
- Overall length 5"

Item No.	Description	Average CFM
5ZL14	Right Angle Air-Powered Die Grinder	3.5



## 4" Air-Powered Angle Grinder

Durable tool for grinding and finishing

1/2 HP motor provides 11,000 RPM. Governor controlled to maintain wheel RPMs under load. 3/8–24" spindle and 1/4" NPT inlet size.

- Uses type 27 depressed center wheels size 4" x 1/4" x 5/8"
- Spiral bevel gear for smooth operation
- 3/8" min. hose size
- Overall length 9-3/4"

Item No.	Description	Average CFM
5ZL31	4" Air-Powered Angle Grinder	4.5



## 1/4" Air-Powered Die Grinder

Designed for heavy grinding or deburring applications

Features lock off throttle that prevents accidental start-ups, and rear exhaust reducing chip blow back.

- 1/4" collet size
- 22,000 RPM free speed
- 1/4" NPT inlet size
- 3/8" min. hose size
- Overall length 6-5/8"

Item No.	Description	Average CFM
5ZL22	1/4" Air-Powered Die Grinder	6



## 1/4" Mini Air-Powered Die Grinder

Easy to use in confined areas

Compact and lightweight. Features a 1/4 HP motor, variable speed self-locking throttle, 25,000 RPM free speed, 3/8" min. hose size, and 1/4" NPT inlet size. Rubber grip for improved operator comfort.

- 1/4" and 1/8" collet size
- Overall length 4-7/8"

Item No.	Description	Average CFM
5ZL15	1/4" Mini Air-Powered Die Grinder	3.5



## 1/4" Mini Air-Powered Die Grinder Kit

Handy durable case for portability

Lock off throttle prevents accidental start-ups. Rear exhaust reduces chip blow back.

- 1/4" collet size
- 22,000 RPM free speed
- 1/4" NPT inlet size
- 3/8" min. hose size

**Kit Includes:**

1/4" Mini Die Grinder 5ZL22, (5) 1/4" and (1) 1/8" Collect Insert Grinding Stones and Durable Plastic Case

Item No.	Description	Average CFM
5ZL23	1/4" Mini Air-Powered Die Grinder Kit	6